

HYBRID HYDROGEN STORAGE CONTAINER AND METHOD OF STORING HYDROGEN IN CONTAINER

Patent number: WO03064916

Publication date: 2003-08-07

Inventor: KURIYAMA NOBUHIRO (JP); TAKEICHI NOBUHIRO (JP); TAKANO TOSHIO (JP); HAMADA KENJIRO (JP); YOKOTA TOMOYUKI (JP); TAKESHITA HIROYUKI (JP); TSURUTA HIDEKAZU (JP)

Applicant: KOKAN DRUM CO LTD (JP); KURIYAMA NOBUHIRO (JP); TAKEICHI NOBUHIRO (JP); TAKANO TOSHIO (JP); HAMADA KENJIRO (JP); NIPPON KOKAN KK (JP); YOKOTA TOMOYUKI (JP); NAT INST OF ADVANCED IND SCIEN (JP); TAKESHITA HIROYUKI (JP); TSURUTA HIDEKAZU (JP)

Classification:

- international: F17C11/00; F17C1/04; B60K15/00; B60K15/06

- european: F17C11/00D

Application number: WO2003JP00977 20030131


Priority number(s): JP20020023273 20020131

Cited documents:

JP61252997
JP56131900
JP2001214206
JP2001524653
JP2000336444

Abstract of WO03064916

A hybrid hydrogen storage container and a method of storing hydrogen in the container, the container comprising a pressure vessel (1) allowed to fill hydrogen therein at a pressure of 30 MPa or higher and having a reinforced layer (2) and a liner layer (3), the pressure vessel (1) further comprising, therein, a hydrogen occlusion body and a carrier (4) for supporting the hydrogen occlusion body, wherein the maximum hydrogen occlusion amount (alpham) of the hydrogen occlusion body per unit volume is $\alpha_{\text{pham}} \geq 100 \text{ (kg/m}^3\text{)}$ and volume ratio (X) of the hydrogen occlusion body to the inside volume of the pressure vessel (1) is $5(\%) \leq X \leq 20(\%)$, where $X = 100 \cdot V_m/V_i (\%)$, V_i : inside volume (L) of pressure vessel, V_m : volume (L) of hydrogen occlusion body in pressure vessel.



Data supplied from the esp@cenet database - Worldwide

BEST AVAILABLE COPY